



LOCOMOTIVE POWER API SC/CC MINERAL

PRODUCT DESCRIPTION:

LOCOMOTIVE POWER SAE 50 is a mineral multi-grade diesel engine oil recommended for the lubrication of diesel engines and naturally aspirated gasoline engines used in commercial and passenger vehicles operating under mild driving conditions.

APPLICATION:

Recommended for the lubrication of diesel / gasoline engines used in trucks and passenger cars operating under mild driving conditions. It can also be used in agriculture equipment, medium-duty trucking, off-road vehicles, construction and quarrying, and certain transmission and mobile hydraulic systems where use of monograde engine oils is recommended by the equipment manufacturer.

FEATURES & BENEFITS:

- Good protection against rust and corrosion.
- Thermal and oxidation stability.
- Controls sludge build up and deposits.
- Long equipment life and reduced maintenance cost.

PERFORMANCE LEVELS : Meets and Exceeds:

- API SC/CC
- MIL-L-2104B

TYPICAL PROPERTIES:

PARAMETERS	TEST METHOD	UNIT	API SC/CC (MINERAL)
Grade			SAE 50
Kinematic Viscosity @ 104°F /40°C	ASTM D-7042	cSt	TBR
Kinematic Viscosity @ 212°F /100°C	ASTM D-7042	cSt	20.2
Viscosity Index (min)	ASTM D-2270	-	95
SP. Gravity @15°C/ 60°F	ASTM D-4052	g/cm ³	TBR
Flash Point (min)	ASTM D-92	°C	220
Pour Point (max)	ASTM D-97	°C	-9

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil into drains or the environment. Dispose to an authorized used oil collection point. For further Information on safety guidelines please refer to MSDS available on our website Locomotive.com